



NITECH IPM[®]

NITECH INTERNATIONAL PACKAGING MACHINES

NitechIPM.com

77205D-LP-PS Low Profile Semi-Automatic Stretch Wrapper with 200% Powered Pre-Stretch

If your looking for a heavy-duty, low maintenance stretch wrapper the Powered pre-stretch 77 series is the answer. With this easy to operate machine you load the 58" variable speed turntable, attach the wrap to the load, select a program, press start and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of top wraps is applied. When the top are completed the film carriage then reverses direction and continues to wrap the load as it lowers. When it reaches the bottom the turntable stops in the same position that it started for easy unloading. The no thread powered pre-stretch offers excellent load containment and the best in film savings.

Maximum Load Size: 56" x 56" x 80" (120" Mast Height Available)

Production Capacity: 40 Loads Per Hour

Machine Dimensions: 111"L x 58"W x 86"H

Weight Capacity: 5,000 lbs.

Electrical Data: 120 VAC 60 Hertz 20 Amps
Conventional Style 3 Prong Power Cord
UL Approved Components
NEMA 12 Enclosure with Gasketed door

Turntable Size: 58" Round Steel Deck with 3" Safety Skirt

Turntable Height: 3 5/8"

Turntable Drive: 3/4 hp DC Motor (Totally Enclosed Fan Cooled)
High Efficient Lubrication Free Helical gear box
Heavy-Duty #50 Roller Chain & Drive Sprockets
Variable Speed Turntable 0 to 15 RPM with Soft Start and Soft Stop
4 Point Cam Follower Turntable Supports(5,000lb. capacity each)
Easy Access Lubrication Points on Turntable
Synthetic Lube in all Gearboxes (-30 to 120°F)
Turntable Indexing Home Alignment

Controls: Toshiba PLC-Programmable Logic Control with 6 pre-programmed sequences
Turntable Variable Speed Dial
Dispenser Variable Speed Dial
Film Tension Variable Dial (Force to Load)
Turntable Jog
Emergency Stop Button
Photo Eye for Automatic Load Height Sensing
On/Pause Button, Start/Resume Switch
3 Indicator Lights, Power, Ready, and Tension
Liquid Crystal Display (LCD)
Non-resettable cycle counter



★ MADE IN THE USA ★

Film Delivery: 20" PPS powered Pre-Stretched Film Delivery, No-Thread Film Carriage
Pre-Stretch Level 200% fixed (Gear switch to 250%, 275%, or 300%)
Accepts 20" Rolls of Stretch Film on 3" core
1/3 Hp DC 90 Volt Motor

Film Carriage: Variable Speed Carriage 0 to 20 FPM
1/4 Hp 90 Volt DC Motor
#40 Chain Carriage Lift
Dispenser Kill Switch Top / Bottom
Adjustable Lower limit Switch
Top Over Wrap
Automatic and Manual Belly Wrapping

Tower Construction: Formed All Steel Tower
80" Wrap Height using 20" Film
Optional wrap heights available up to 116"
Maint. Free UHMW Full Tower Slides
Dispenser Kill Switch Top/Bottom

Frame Construction: All Welded Steel Construction
Heavy-Duty Structural Tube & Plate
Easy Access to all Components
Industrial Powder Coated Paint Finish
Forklift Portable from Front or Rear

Warranty: 3 year limited warranty (100% of all components)

Shipping Weight: 1,520 lbs.

NitechIPM
911 23rd St. East
Columbus, NE. 68602-1023

1-800-397-1100

Ph: 402-563-3188
Fax: 402-563-2792

NitechIPM.com

© Copyright 2013 NitechIPM. All Rights Reserved. Specifications, design, accessories or pricing without notice. Artwork does not indicate model or year and may only be reproduced with written permission from NitechIPM