



## 77205-LPV

### Low Profile Variable Speed Turntable with Toggle Switch Operated Variable Speed Quick-Load Film Dispenser

#### OVERVIEW

If your wishing to become more efficient get better load security and save material the 77205-LPV has all the features your looking for. These stretch wrap machines come equipped with a variable speed film carriage to move the stretch wrap dispenser up and down and a variable speed turntable. Just load the 58" round turn table, attach the film, set the film carriage's vertical speed and the turntable speed dispenser's stretch wrap tension. While the load turns you can vary the speed as you control the up and down movement of the Quick-Load dispenser with a toggle switch. Increase productivity, optimize film usage and have tighter load security.



#### SPECIFICATIONS

|                      |  |
|----------------------|--|
| Maximum Load Size:   | 56" x 56" x 76" (120" Mast Height Available)   |
| Production Capacity: | 40 Loads Per Hour  |
| Machine Dimensions:  | 111"L x 58"W x 83"H  |
| Weight Capacity:     | 5,000 lbs.   |
| Electrical Data:     | 120 VAC 60 Hertz 20 Amps<br>Conventional Style 3 Prong Power Cord<br>UL Approved Components  |
| Turntable Size:      | 58" Round Steel Deck<br>with 2" Safety Skirt   |
| Turntable Height:    | 3 5/8"   |
| Turntable Drive:     | 3/4 Hp Dc Motor (Totally Enclosed Fan Cooled)<br>Variable Speed Turntable 0-15 RPM with Soft Start and Soft Stop<br>4 Point Cam Follower Turntable Supports<br>Easy Access Lubrication Points on Turntable<br>Heavy-Duty #50 Roller Chain and Drive Sprocket<br>Synthetic Lube In All Gearboxes (-30 to 120°F) |

|                     |   |
|---------------------|---|
| Controls:           | Power On / Off with Indicator<br>Turntable Speed Dial<br>Dispenser Speed Dial<br>Film Carriage Up / Down Controls<br>2 Diagnostic Lights<br>Emergency Stop Button   |
| Film Delivery:      | Quick Load Film Dispenser<br>Manual Adjusted Variable Film Stretch (Load Brake)<br>Stretch level 30% - 150% Force to Load<br>Accepts 12" to 20" Rolls of Stretch Film   |
| Film Carriage:      | 76" Wrap Height (Optional Wrap Height Available)<br>Top Over Wrap<br>Variable Speed Carriage 0 to 20 FPM<br>1/4 HP 90 Volt DC Motor<br>12 Point UHMW Carriage Guidance Supports<br>Dispenser Kill Switch Top / Bottom |
| Frame Construction: | Custom Formed 3/8" Steel Channel<br>All Welded Steel Construction<br>Forklift Portable from Front and Rear  |
| Warranty:           | 3 Year Limited Warranty<br>(100% of all components).  |
| Shipping Weight:    | 1,120 lbs.  |