

77205-V High Profile Variable Speed Turntable with **Toggle Switch Operated Quick-Load Film Delivery**

The 77205-V offers the best value for the dollar for those wishing to upgrade from hand wrapping. These stretch wrap machines come equipped with a variable speed fi Im carriage to move the Quick-Load fi Im dispenser up and down and a variable speed turntable. Just load the 48" round or octagon turn table, attach the film, set the film carriage's vertical speed and the turntable speed dispenser's stretch wrap tension. While the load turns you can vary the speed as you control the up and down movement of the dispenser with a toggle switch. Increase productivity, optimize film usage and have tighter load security.

Maximum	52" x 52" x 77"
	- ·· · · ·

Load Size: (116" Mast height available).

Production

30 Loads per hour.

Capacity: Machine

111"L x 48"W x 94"H.

Dimensions:

Weight 4,000 Lbs.

Capacity: Electrical

120 VA 60 hrtz 20 amps.

Conventional style 3 prong 20' power Data:

cord

UL approved components.

Nema 12 enclosure with gasketed door.

Turntable 48" Round steel diamond deck with 5" Size:

safety skirt.

Turntable Height:

11 3/4"

Turntable Drive:

3/4 Hp DC motor (totally enclosed fan

cooled).

Variable speed turntable 0 to 12 rpm

with soft start and soft stop.

Lubrication free enclosed gear drive

design.

Synthetic lube in all gearboxes (-30 to

120 °F).

Controls: Power on / off with indicator.

Film carriage speed dial.

Film carriage up / down switch.

2 Diagnostic lights.

Emergency stop button.

Film 20" Quick load film delivery.

NITECHIPM

Delivery: Manual adjusted variable film stretch

(load brake).

Stretch level 30% - 150% force to load.

Accepts 12" to 20" rolls of stretch film.

Film 77" Wrap height (optional extended

Carriage: wrap height available).

Variable speed carriage 0-20 fpm.

1/4 Hp 90 volt dc motor.

#40 Chain carriage lift.

Film carriage kill switch top/bottom.

Adjustable lower limit switch.

Formed all steel tower. Tower

Construction: Maintenance free UHMW full tower slides.

Maint. free UHMW full tower slides. Access compartment for motor brush

replacement.

Frame All welded steel construction.

Construction: Heavy-duty structural tube and plate.

Easy access to all components.

Industrial powder coated paint finish. Forklift portable from front and rear.

Warranty: 4 Year limited warranty.

5 Year structural warranty.

10 Year turntable reducer warranty.

1,150 lbs. Shipping Weight:

© 2025 NitechIPM. All rights reserved. Specs and design subject to change. Artwork may not reflect model/year



