



NITECH IPM®
NITECH INTERNATIONAL PACKAGING MACHINES

77205D-LPPS Power Pre-Stretch Film System with Semi-Automatic Operation, Color Touchscreen and Heavy Duty Capacity

Overview

The NITECH 77205D-LPPS is designed for operations that need high-capacity, semi automatic wrapping with reduced film usage. Built on a heavier-duty platform and equipped with a powered pre-stretch system, it combines strong load handling with efficient film application.

Load the turntable, attach the film to the pallet, select a program, and press start. The machine automatically wraps the load as the carriage travels upward, sensing the top with a photo eye before applying preset top wraps. The carriage then reverses direction and continues wrapping as it lowers, stopping in the same position for easy unloading.

The powered pre-stretch system extends the film before application, allowing more yield from each roll while maintaining consistent load containment. This helps reduce film consumption while supporting higher-volume and more demanding wrapping applications.

Features

- ✓ Low-profile turntable for pallet jack loading
- ✓ Power pre-stretch film delivery system
- ✓ Automatic wrap cycle with photo eye load height sensing
- ✓ Programmable wrap cycles with preset top and bottom wraps
- ✓ Film tension adjustment (force-to-load control)
- ✓ Variable speed turntable with soft start and stop
- ✓ Intuitive control system for simple operation
- ✓ Heavy-duty all steel construction
- ✓ 5,000 lb load capacity
- ✓ Scale and ramp options available



NITECH IPM®
NITECH INTERNATIONAL PACKAGING MACHINES



info@nitechipm.com



800-237-6496



Specifications

Machine Profile	Low Profile
Maximum Load Size	56" x 56" x 80"
Product Capacity	30 Loads Per Hour
Machine Dimensions	111"L x 60"W x 94"H
Weight Capacity	5,000 LB.
Electrical Data	120 VAC 60 Hertz 20 Amps, Conventional Style 3 Prong 20', Power Cord, NEMA 12 Enclosure with Gasketed door, UL Approved Components
Turntable Size	60" Round Turntable w/3" Safety Skirt
Turntable Height	3 5/8"
Turntable Drive	3/4 hp DC Motor (Totally Enclosed Fan Cooled), 4 Point Cam follower Supports (5,000 lb. capacity each), Heavy-Duty #50 Roller Chain and Drive Sprockets, High Efficient Lubrication Free helical gear box, Synthetic Lube in all Gearboxes (-30 to 120 Degrees), Turntable Indexing Home Alignment, Variable Speed 0-15 RPM with Soft Start and Soft Stop
Controls	7" Color Touch Screen with 8 Modifiable Programs, Manual Back-Up Operating System. Real Time Machine Alerts From Touch Screen, Full Color Operators Manual on Touch Screen, Turntable Variable Speed Dial, Carriage Variable Speed Dial, Film Tension Dial (Force to Load), Turntable Jog, Emergency Stop Button, On/Pause Button, Start/Resume Switch, 3 Indicator Lights Power, Ready and Tension, Liquid Crystal Display (LCD), Non-Resettable cycle counter, Resettable counter, Photo Eye for Automatic Load Height Sensing
Film Delivery	20" PPS Powered Pre-Stretch Film Delivery, Easy Thread Film Carriage, Pre-Stretch level 200% fixed. (Gear switch to 250%, 275% or 300%), Accepts 20" Rolls of Stretch Film on 3" Core. 1/4 HP DC 90 Volt Motor
Film Carriage	#40 Chain Carriage Lift, 1/4 HP 90 Volt DC Motor, Adjustable Lower limit Switch, Automatic and Manual Belly Wrapping, Dispenser Kill Switch Top/ Bottom, Top Over Wrap, Variable Speed Carriage 0-20 FPM
Tower Construction	80" Wrap height using 20" Film, Adjustable Lower Limit Switch, Carriage Kill Switch Top and Bottom, Formed All Steel Tower, Maintenance Free UHMW Full Tower Slides, Optional wrap heights available up to 120"
Frame Construction	All Welded Steel Construction, Easy Access to all Components, Forklift Portable from Front and Rear, Heavy-Duty Structural Tube and Plate, Industrial Powder Coated Paint Finish
Power Required:	115 volts, 50/60 hertz, 20 Amp Service
Technical Documentation	Complete Electrical Schematics, Complete Operators Manual, Illustrated Parts Break down
Warranty	4 Year Limited Warranty (100% of All Components), 10-Year Structure Warranty, 5-year turntable gearbox
Average Cycle Time	1 minute 20 seconds wrapping 40" x 48" x 60" pallet with 12 wraps. Load configuration will vary wrap cycle.
Shipping Weight	1,710 lbs



NITECH IPM
NITECH INTERNATIONAL PACKAGING MACHINES



info@nitechipm.com



800-237-6496

