



NITECH IPM®
NITECH INTERNATIONAL PACKAGING MACHINES

77201-VS Variable Speed Turntable With Foot Switch Control For Simple, Ergonomic Hand Wrapping

Overview

The NITECH 77201-VS is designed for operations that need a simple wrapping solution with added control over turntable speed. It maintains the basic turntable wrapping approach while allowing the operator to adjust rotation speed based on the load weight and stability.

Load the turntable, attach the film, and use the foot switch to begin rotation. As the load turns, the operator applies film by hand while adjusting the turntable speed from the footswitch to match the load and wrapping preference.

This added speed control provides more flexibility than a fixed-speed unit, making it easier to handle a wider range of pallet weights & types while keeping the wrapping process simple.

Operators now remain stationary while the load rotates, simplifying the wrapping process while reducing worker fatigue and improving overall efficiency.

Features

- ✓ Foot switch controlled turntable operation
- ✓ Variable speed turntable With footswitch control
- ✓ Simple on/off control for easy use
- ✓ Open platform for manual film application
- ✓ Durable all steel construction
- ✓ Fork-lift Portable
- ✓ Industry-leading warranty (4-year components, 10-year structure, 10-year gearbox)
- ✓ 4,000 lb load capacity



NITECH IPM®
NITECH INTERNATIONAL PACKAGING MACHINES



info@nitechipm.com



800-237-6496



Specifications

Machine Profile	High Profile
Maximum Load Size	65" x 65"
Product Capacity	25 Loads per Hour
Weight Capacity	4,000 lbs
Electrical Data	120 VAC 60 Hertz 20 Amps, Conventional Style 3 Prong 20' Power Cord, UL Approved Components
Turntable Size	48" Round Steel Diamond Deck w/4" Safety Skirt
Turntable Height	11 3/4"
Turntable Drive	3/4 hp DC Motor (Totally Enclosed Fan Cooled), Lubrication Free Enclosed gear drive design, Soft Start and Soft Stop, Synthetic Lube in all Gearboxes (-30 to 120 Degrees), Variable Speed 0-12 RPM (Optional Speeds Available)
Controls	Variable-speed guarded IP65 sealed footswitch with start/stop control and 0-12 rpm table speed adjustment operated directly from the footswitch
Frame Construction	Custom Formed Steel Channel, Easy Access to all Components, Forklift Portable, a Heavy-Duty Structural Tube and Plate, Industrial Powder Coated Paint Finish
Technical Documentation	Complete Electrical Schematics, Complete Operators Manual, Illustrated Parts Break down
Warranty	4 Year Limited Warranty (100% of All Components), 10-Year Gear Reducer Warranty, 10-Year Structural Warranty
Shipping Weight	650 lbs.
Film Carriage	N/A
Film Delivery	N/A
Tower Construction	N/A



NITECH IPM
NITECH INTERNATIONAL PACKAGING MACHINES



info@nitechipm.com



800-237-6496

